# REPARABILITY INDEX WORKSHEET OF ROBOTIC VACUUM GENERAL INSTRUCTIONS

### **PURPOSE OF THE FILE**

This Excel file calculates the reparability index of a robotic vacuum

### **REGULATORY FRAMEWORK**

Article L. 541-9-2 of the French Environmental Code states that: Manufacturers, importers, marketers and other retailers which put electrical and electronic equipment (EEE) on the French market have to inform, free of charge, downstream sellers and any person who made the request of "the reparability index" of their products, as well as the paramaters explaining how such index was established. This reparability index will inform consumers about the ability to repair the product category concerned. All information entered in this file must be truthful and verifiable.

The methods and rules of implementation for the reparabilty index are specified in the reparabilty index Decree N°2020-1757 2020-12-29 for electrical and electronic equipment (EEE), the Decision 2020-12-29 on display conditions and parameters for calculating the reparability index and the Decision 2022-05-04 on criteria, subcritera, rating system and display of the reparability index of robotic vacuum.

A complementary instructions manual provides explanatory informations and additional instructions on how to apply Decree and Orders of the reparability index of electrical and electronic equipement.

### **FILE CONTENT**

General instructions	Description of the purpose of this Excel file, description of regulatory framework of the reparabily index and description of file content and how it will be completed.						
Product information	Description of the product and the assessment of its repairability index.						
C1_Documentation	Detailed criteria used to calculate the reparability index of the product.						
C2_Disassembly	On each tab page, all 'orange boxes' must be completed by selecting the right information from the 'drop-down list' or by directly entering the right information in						
C3_Availability of spare parts	the box (e.g. criterion 4 : price and file to be send).						
C4_Price	When the information is enterred, the concerned box changes to 'green'. No box should be left unanswered. Note that the cells must be completed one by one						
C5_Specific	they must not be stretched).						
Final score	This tab automatically calculate final score of the reparability index of the product and also scores per criteria and sub-criteria, before and after weighting.						
Note finale	This tab is the French translation of the "Final score" tab. It is automatically completed. This tab is to be sent to all applicants.						
Annex 1	Details about the therminology used for the reparability index.						
Annex 2	Details about the list of "basic" tools and their reference standards.						
Annex 3	Details and application case about the concept of disassembly step.						

REINTIALISER LES CHOIX

This button resets all data entered into the file. If you want to execute this action, please enable macros and click on the button.

WARNING: this action cannot be undone.

# INFORMATIONS RELATING TO THE PRODUCT AND THE CALCULATION OF ITS REPAIRABILITY INDEX

robotic vacuum

DATE OF CALCULATION	2022/12/27
REQUESTOR OF THE ASSESSMENT	
LAST NAME	Rebecca
FIRST NAME	Zhu
MAIL	zhuhongmei@roborock.com
PHONE NUMBER	8615323809016
RESPONSIBLE FOR EVALUATION	
LAST NAME	Rebecca
FIRST NAME	Zhu
MAIL	zhuhongmei@roborock.com
PHONE NUMBER	8615323809016
RATED PRODUCT	
Producer's or importer's name or trademark	roborock
Producer or importer adress	TAI SANG BANK BUILDING, 130-132 DES VOEUX ROAD CENT
Producer's or importer's model identifier	S7 Pro Ultra

**CRITERION 1: DOCUMENTATION** Robotic vacuum

Column B

Column C

#### SUB-CRITERION 1.1: COMMITMENT ON THE AVAILABILITY OVER TIME (WITHOUT CHARGE) OF THE TECHNICAL DOCUMENTATION AND THE OTHER DOCUMENTATION RELATED TO USER AND MAINTENANCE INSTRUCTIONS

#### ADDITIONAL INFORMATIONS:

Documents/informations: The information can be freely distributed at the initiative of the producer in various physical or dematerialized documents. Scoring points are awarded if the information referred to is available in any document.

Commitment on the availability over time of the documentation

Language of documents: In accordance with the law of August 4, 1994 on the use of the French language, information intended for consumers must be drawn up in French; English is tolerated for very technical aspects intended for professional repairers (example: technical bulletins).

Technical bulletins: This wording covers announcements made by the producer to professional repairers, informing them, for example, of recently discovered bugs, of the corrections to be made, of the supply disruption of parts which have been replaced by others. Points are

awarded if the edition of a technical bulletin is planned on an ongoing basis (when necessary).

Information on access to professional repairers: The producer or importer is free to indicate to consumers the professional repairers of his

choice, but it is advisable to mention at least the repairer directories listed by Ademe : www.annuaire-reparation.fr

Instructions for self-repair: Points corresponding to years of availability are only granted if one or more operations are specified to consumers for self-repair, with adequate safety instructions, in a specific section under the title "self-repair", for example in the technical manual or of the instructions for use and maintenance. Article L 441-5 of the Consumer Code specifies the responsibility of the producer regarding self-repair

	(in years)	Repairers		Consumers	
	Type of documentation	Duration of availability	Subtotal	Duration of availability	Subtotal
1.1.A	The unequivocal identification of the product (type of product, trademark, trade name, model, and possibly, serial number)	if X ≥ 13 years	13	if X ≥ 13 years	13
1.1.B	A dissasembly map or exploded view	if X ≥ 13 years	13	if X ≥ 13 years	13
1.1.C	Wiring and connection diagrams	if X ≥ 13 years	13	Not available	0
1.1.D	Electronic boards diagrams	if X ≥ 13 years	13	Not available	0
1.1.E	List of necessary repair and test equipment	if X ≥ 13 years	13	if X ≥ 13 years	13
1.1.F	Technical manual of instructions for repair	if X ≥ 13 years	13	if X ≥ 13 years	13
1.1.G	Diagnostic fault and error codes	if X ≥ 13 years	13	if X ≥ 13 years	13
1.1.H	Component and diagnosis information	if X ≥ 13 years	13	if X ≥ 13 years	13
1.1.1	Instructions for software and firmware (including reset software)	if X ≥ 13 years	13	Not available	0
1.1.J	information on how to access data records of reported failure incidents stored on the product	if X ≥ 13 years	13	if X ≥ 13 years	13
1.1.K	Technical bulletins	if X ≥ 13 years	13	Not available	0
1.1.L	Specific guidance for self-repair (recommended operations, safety and repair instructions, any implications for the guarantee)*			if X ≥ 13 years	13
1.1.M	How to get access to professional repairers			if X ≥ 13 years	13
1.1.N	Failures detection and required action (consumers approach)			if X ≥ 13 years	13
1.1.0	User and maintenance instructions			if X ≥ 13 years	13
	Total sub-criterion 1.1		143		143

<sup>\*</sup>Points corresponding to years of availability are only awarded if one or more operations are specified to consumers for self-repair, with adequate safety

#### CRITERION 2 : DISASSEMBLY, ACCESSIBILITY, TOOLS, FASTENERS

robotic vacuum

SUB-CRITERION 2.1: EASE OF DISASSEMBLY OF SPARE PARTS - BROKEN / MALFUNCTIONING PARTS (LIST 2)

ADDITIONAL INFORMATIONS:
Details of the dismantling steps can be found on the right side of this sheet and in Annex 3 grid.

A part is considered non-removable if it is not individually accessible and cannot be detached from the equipment or a sub-assembly, with a view to its replacement. In this case, the points for the corresponding criterion 2.1 are not awarded.

A link is established between the rating of sub-criterion 2.1 and that of sub-criterion 3.1, in the case where a part cannot be dismantled: the zero score is then passed on from one sub-criterion to another.

PARTICULAR CASE OF ROBOTIC VACUUM
The dust collector or bag access trap is not taken into account in criterion 2.1 Ease of disassembly

	Ease of disassembly	Rating						
	List 2 : Broken / malfunctioning parts	Number of steps required to disassemble the spare part	Subtotal					
2.1.A	Battery	if DDi < 4	3					
2.1.B	Side brush motor	if DDi < 6	3					
2.1.C	Brush bar	if DDi < 4	3					
2.1.D	Dust collector or bag acces trap							
2.1.E	Follower wheels	if DDi < 4	3					
	Total sub-criterion 2.1		12					
	Total Sub-criterion 2.1		10.0					

SUB-CRITERION 2.2: NECESSARY TOOLS TO REMOVE SPARE PARTS - BROKEN / MALFUNCTIONING PARTS (LIST 2)

ADDITIONAL INFORMATIONS:

- Necessary tools to unitarily disassemble a spare part include all tools used to get access and disassemble the concerned part without causing damage to the product (which might include getting access to fasteners).

- Tools used are classified according to the complexity of the operation to final users and the availability of tools.

- In case of using different types of tools in the disassembly and reassembly sequences of a spare part, the worst score shall be considered.

	Necessary tools for disassembly	Rating						
	List 2 : Broken / malfunctioning parts	Type of tools used for disassembly	Subtotal					
2.2.A	Battery	D : Removable with no tool with tools supplied with the product or with basic	4					
2.2.B	Side brush motor	D : Removable with no tool with tools supplied with the product or with basic	4					
2.2.C	Brush bar	D : Removable with no tool with tools supplied with the product or with basic	4					
2.2.D	Dust collector or bag acces trap	D : Removable with no tool with tools supplied with the product or with basic	4					
2.2.E	Follower wheels	D : Removable with no tool with tools supplied with the product or with basic	4					
	Total sub-criterion 2.2		20					
	Total sub-criterion 2.2		10.0					

#### SUB-CRITERION 2.3 : CHARACTERISTICS OF FASTENERS FOR THE ASSEMBLY OF SPARE PARTS (LISTS 1 AND 2)

ADDITIONAL INFORMATIONS:

- Fasteners: A hardware device that mechanically or magnetically connects or fixes two or more objects, parts or pieces. A fastener is generally non-permanent, i.e., it can be easily removed or disassembled without damaging the objects, parts or pieces connected or fixed together (e.g., screws or clips). Welds and some glues are in contrast to permanent fixings. Adhesives are considered non-reusable fasteners unless new ones are supplied with the spare part.

- Fasteners removed are classified according to their accessibility, reusability, amovibility and also their constraints imposed to the product

eparability (e.g. fasteners causing damage or leaving welding or glue residues which preclude reusabiliy of the removed part). In case of removing different types of fasteners during the disassembly step of a spare part, the worst score shall be consider

	Fasteners characteristics	Rating							
	List 1 : Functional parts List 2 : Broken / malfunctioning parts	Type of fasteners	Subtotal						
2.3.A	Guidance motor (with or without wheel drive)	C : Removable and reusable	2						
2.3.B	Filter / pre-filter	C : Removable and reusable	2						
2.3.C	Electronic control board	C : Removable and reusable	2						
2.3.D	Power electronic card	C : Removable and reusable	2						
2.3.E	Bumper captor	C : Removable and reusable	2						
2.3.F	Charging station	C : Removable and reusable	2						
2.3.G	Storage station	C : Removable and reusable	2						
2.3.H	On/Off switch	C : Removable and reusable	2						
2.3.1	Drive wheels (with or without guidance motor)	C : Removable and reusable	2						
2.3.J	Main motor	C : Removable and reusable	2						
2.3.K	Battery	C : Removable and reusable	2						
2.3.L	Side brush motor	C : Removable and reusable	2						
2.3.M	Brush bar	C : Removable and reusable	2						
2.3.N	Dust collector or bag acces trap	C : Removable and reusable	2						
2.3.0	Follower wheels	C : Removable and reusable	2						
	Total sub-criterion 2.3		30						
	Total Sub-Griterion 2.5		10.0						

### CRITERION 3: AVAILABILITY OF SPARE PARTS

Robotic vacuum

SUB-CRITERION 3.1: COMMITMENT ON THE AVAILABILITY OVER TIME OF SPARE PARTS - BROKEN/MALFUNCTIONINGPARTS (LIST 2)

ADDITIONAL INFORMATIONS
Definition of spare parts distributor. The definition of a spare parts distributor is given in the glossary in appendix 1 of the gird

Commitments on the availability of spare parts and delivery times (except Sunday and fest days): To award points to the A columns, the producer should have his own in-house repair service (example: via the after-sales service). Whether for the period of availability of spare parts or the delivery time, the producer or the importer must retain, among all of their practices towards authorized and independent repairers, the period or the most penalizing time for each spare part. In the event that the producer or importer does not make spare parts directly available to independent repairers, then points are not awarded in column C of criterion 3.1, 3.2, 3.3 and 3.4. In addition, in the event that the producer or importer does not have an approved repairers network, the points are awarded based on the most penalizing practices towards independent repairers.

Delivery time: The delivery time is understood in working days between the day of the order and the day of arrival at the actor concerned.

Con	nmitment on the availability over time of spare parts (in years)	Column A Producer		Column B Spare parts reta		Column C Repairers		Column D Consumer			
	List 2 : Broken / malfunctioning parts	Duration of availability	Subtotal	Duration of availability	Subtotal	Duration of availability	Subtotal	Duration of availability	Subtotal		
3.1.A	Battery	if X < 9 years	0	if X < 9 years	0	if X < 9 years	0	if X < 9 years	0	ĺ	
	Side brush motor	if X ≥ 13 years	13	if X ≥ 13 years	13	if X ≥ 13 years	13	if X ≥ 13 years	13	İ	
	Brush bar	if X ≥ 13 years	13	if X ≥ 13 years	13	if X ≥ 13 years	13	if X ≥ 13 years	13	İ	
3.1.D	Dust collector or bag acces trap	if X ≥ 13 years	13	if X ≥ 13 years	13	if X ≥ 13 years	13	if X ≥ 13 years	13	İ	
3.1.E	Follower wheels	if X < 9 years	0	if X < 9 years	0	if X < 9 years	0	if X < 9 years	0	İ	
	Total sub-criterion 3.1		39		39		39		39	156	ĺ
	10(a) 305-61(6101) 3.1									6.0	Ĺ

SUB-CRITERION 3.2: COMMITMENT ON THE AVAILABILITY OVER TIME OF SPARE PARTS - FUNCTIONAL PARTS (LIST 1)

Cor	nmitment on the availability over time of spare	Column A		Column B		Column C		Column D	)
	parts (in years)	Producer		Spare parts reta	ailers	Repairers		Consumer	rs
	List 1: Functional parts	Duration of availability	Subtotal	Duration of availability	Subtotal	Duration of availability	Subtotal	Duration of availability	Subtotal
3.2.A	Guidance motor (with or without wheel drive)	if X < 9 years	0						
3.2.B	Filter / pre-filter	if X < 9 years	0						
3.2.C	Electronic control board	if X < 9 years	0						
3.2.D	Power electronic card	if X < 9 years	0						
3.2.E	Bumper captor	if X < 9 years	0						
3.2.F	Charging station	if X < 9 years	0						
3.2.G	Storage station	if X < 9 years	0						
3.2.H	On/Off switch	if X < 9 years	0						
3.2.1	Drive wheels (with or without guidance motor)	if X < 9 years	0	if X < 9 years	0	if X < 9 years	0	if X < 9 years	0
3.2.J	Main motor	if X < 9 years	0						
	Total sub-criterion 3.2		0		0		0		0
	TOTAL SAID CITESTION S.E.								

SUB-CRITERION 3.3: COMMITMENT ON THE DELIVERY TIME OF SPARE PARTS - BROKEN/MALFUNCTIONINGPARTS (LIST 2)

Co	mmitment on the delivery time of spare parts (in working days)	Column A Producer		Column B Spare parts reta	ilore	Column C Repairers		Column D Consumers			
	List 2 : Broken / malfunctioning parts	Delivery time	Subtotal		Subtotal	Delivery time	Subtotal	Delivery time Subtota			
3.3.A	Battery	if X >10 days	0	if X >10 days	0	if X >10 days	0	if X >10 days	0		
3.3.B	Side brush motor	if 5 days ≥ X > 3 days	2	if 5 days ≥ X > 3 days	2	if 5 days ≥ X > 3 days	2	if X >10 days	0		
3.3.C	Brush bar	if 5 days ≥ X > 3 days	2	if 5 days ≥ X > 3 days	2	if 5 days ≥ X > 3 days	2	if X >10 days	0		
	Dust collector or bag acces trap	if 5 days ≥ X > 3 days	2	if 5 days ≥ X > 3 days	2	if 5 days ≥ X > 3 days	2	if X >10 days	0		
3.3.E	Follower wheels	if 5 days ≥ X > 3 days	2	if 5 days ≥ X > 3 days	2	if 5 days ≥ X > 3 days	2	if X >10 days	0		
	Total sub-criterion 3.3		8		8		8		0		

SUB-CRITERION 3.4: COMMITMENT ON THE DELIVERY TIME OF SPARE PARTS - FUNCTIONAL PARTS (LIST 1)

C	ommitment on the delivery time of spare parts (in working days)	Column A Producer		Column B Spare parts reta	nilers	Column C Repairers		Column D Consumers		
	List 1 : Functional parts	Delivery time	Subtotal	Delivery time	Subtotal	Delivery time	Subtotal	Delivery time	Subtotal	
3.4.A	Guidance motor (with or without wheel drive)	if 5 days ≥ X > 3 days	2	if 5 days ≥ X > 3 days	2	if 5 days ≥ X > 3 days	2	if 5 days ≥ X > 3 days	2	
3.4.B	Filter / pre-filter	if 5 days ≥ X > 3 days	2	if 5 days ≥ X > 3 days	2	if 5 days ≥ X > 3 days	2	if 5 days ≥ X > 3 days	2	
3.4.C	Electronic control board	if 5 days ≥ X > 3 days	2	if 5 days ≥ X > 3 days	2	if 5 days ≥ X > 3 days	2	if X >10 days	0	
3.4.D	Power electronic card	if 5 days ≥ X > 3 days	2	if 5 days ≥ X > 3 days	2	if 5 days ≥ X > 3 days	2	if X >10 days	0	
3.4.E	Bumper captor	if 5 days ≥ X > 3 days	2	if 5 days ≥ X > 3 days	2	if 5 days ≥ X > 3 days	2	if 5 days ≥ X > 3 days	2	
3.4.F	Charging station	if 5 days ≥ X > 3 days	2	if 5 days ≥ X > 3 days	2	if 5 days ≥ X > 3 days	2	if 5 days ≥ X > 3 days	2	
3.4.G	Storage station	if 5 days ≥ X > 3 days	2	if 5 days ≥ X > 3 days	2	if 5 days ≥ X > 3 days	2	if 5 days ≥ X > 3 days	2	
3.4.H	On/Off switch	if 5 days ≥ X > 3 days	2	if 5 days ≥ X > 3 days	2	if 5 days ≥ X > 3 days	2	if 5 days ≥ X > 3 days	2	
3.4.1	Drive wheels (with or without guidance motor)	if 5 days ≥ X > 3 days	2	if 5 days ≥ X > 3 days	2	if 5 days ≥ X > 3 days	2	if 5 days ≥ X > 3 days	2	
3.4.J	Main motor	if 5 days ≥ X > 3 days	2	if 5 days ≥ X > 3 days	2	if 5 days ≥ X > 3 days	2	if 5 days ≥ X > 3 days	2	
	Total sub-criterion 3.4		20		20		20		16	

#### ADDITIONAL INFORMATIONS:

Deduction of delivery costs: The principle adopted is to make a calculation excluding transport or delivery costs. If the latter are included in the tariffs of the general terms and conditions of sale, it is up to the producer or importer to deduct them in order to calculate the ratio. In particular for the price of spare parts, two methods are possible for deducting transport or delivery costs: individually for each of the parts in list 2 or on a flat-rate basis (in absolute value or as a percentage). The same applies to the price of new equipment.

Spare part(s) forming part of a batch: If one or more of the parts in list 2 are part of a batch offered for sale or of any other subset of

inseparable parts, the price of the part concerned is the price of this batch or subset.

Part not available: In the event that, at the time the index is calculated, a part from list 2 is not available, the number of points

Part not available: In the event that, at the time the index is calculated, a part from list 2 is not available, the number of points awarded for criterion 4 relating to the price of spare parts is 0.

Parts not managed by the producer or importer: If parts from list 2 are not managed by the producer or importer, the price of the parts to be considered is then that of the supplier's general terms and conditions of sale at the time of the index calculation.

Options for products with the same reference: If options are offered for the same reference, and do not influence the technical characteristics for the purpose of calculating the index, then the calculation of the price ratio to be achieved is based on the price of spare parts and the price of the most current version of the product concerned.

Absence of a part: If the equipment does not include a part listed in list 1 or 2 of the category concerned, then the price of the absent part does not appear in the calculation of the ratio.

	RATING								
PRICE Criterion	Value (euros)	Score (%)	POINTS (/100)	FINAL SCORE (/10)					
Pre-tax price of the most expensive spare part (list 2)	48.05								
Average pre-tax price of other spare parts (list 2)	80.12	5.83%	100	10.0					
Manufacturer's pre-tax price of concerned model	1099								

The number of points obtained for this criterion is determined as follows:

- if the result is greater than 0.3 then the number of points is 0; if the result is less than 0.1 then the number of points is 100;
- if the result is between 0.1 and 0.3 then the number of points is determined according to the following correspondence table :

Ratio	0,1	0,11	0,12	0,13	0,14	0,15	0,16	0,17	0,18	0,19	0,2	0,21	0,22	0,23	0,24	0,25	0,26	0,27	0,28	0,29	0,3
Points	100	95	90	85	80	75	70	65	60	55	50	45	40	35	30	25	20	15	10	5	0

CRITERION 5 : SPECIFIC CRITERION Robotic vacuum

### REPAIRABILITY INDEX CALCULATION AND PRESENTATION OF THE PARAMETERS WHICH ALLOWED TO ESTABLISH IT Robotic vacuum

Date of calculation	2022/12/27
Producer's or importer's name or trademark	roborock
Producer or importer adress	ROOM 1303 13/F TAI SANG BANK BUILDING, 130-132 DES VOEUX ROAD CENTRAL CENTRAL HK
Producer's or importer's model identifier	S7 Pro Ultra

This "FINAL\_SCORE" tab in English is purely indicative. In order to meet regulatory obligations, only the "NOTE\_FINALE" tab in French (see the next tab) is to be sent. Note: The results are automatically reported in the French tab.

Criteria	Sub-criteria	Score of subcriterion /10	Weighting factor of subcriterion	Score of criterion /20	Total criteria scores /100
	1.1 Availability of the technical documentation and other documentation related to user and maintenance instructions	8.5	2	16.9	
0	2.1 Ease of disassembly parts from List 2*	10.0	1		
DISASSEMBLY, ACCESSIBILITY,	2.2 Necessary tools (List 2)	10.0	0.5	20.0	
TOOLS, FASTENERS	2.3 Fasteners characteristics parts from List 1** and List 2	10.0	0.5		
	3.1 Availability over time parts from List 2	6.0	1		
CRITERION 3 : AVAILABILITY OF	3.2 Availability over time parts from List 1	0	0.5	8.5	83.4
	3.3 Delivery time parts from List 2	4.0	0.3	0.5	03.4
	3.4 Delivery time parts from List 1	6.3	0.2		
CRITERION 4 : PRICE OF SPARE PARTS	4. Ratio between price of parts from list 2 to the price of the product	10.0	2	20.0	
	5.1 Accesibility of usage-counter to consumers	10.0	1		
CRITERION 5 : SPECIFIC CRITERION	5.2 Free remote assistance	6.0	0.5	18.0	
	5.3 Possibility to reset softwares	10.0	0.5		
	F	Reparabilit	y index o	n 10	8.3

<sup>\*</sup> list 2: list of a maximum of 3 to 5 spare parts (depending on the category of equipment concerned) whose broken or malfunctioning parts are the most frequent;
\*\* list 1: list of a maximum of 10 other spare parts (depending on the category of equipment concerned) whose good condition is necessary for the operation of the equipment.

#### CALCUL DE L'INDICE DE RÉPARABILITÉ ET PRÉSENTATION DES PARAMÈTRES AYANT PERMIS DE L'ÉTABLIR

Aspirateur robot

# FICHE D'INFORMATION À TRANSMETTRE AUX DEMANDEURS (cf. Article L. 541-9-2 du Code de l'environnement)

Date du calcul	2022/12/27
Nom ou marque commerciale du producteur ou de l'importateur	roborock
Adresse du producteur ou de l'importateur	ROOM 1303 13/F TAI SANG BANK BUILDING, 130-132 DES VOEUX ROAD CENTRAL CENTRAL HK
Référence du modèle donnée par le producteur ou l'importateur	S7 Pro Ultra

Critère	Sous-critère	Note du sous-critère sur 10	Coefficient du sous critère	Note du critère sur 20	Total des notes des critères sur 100
CRITÈRE 1 : DOCUMENTATION	1.1 Durée de disponibilité de la documentation technique et relative aux conseils d'utilisation et d'entretien	8.5	2	16.9	
OINT LIKE L.	2.1 Facilité de démontage des pièces de la liste 2*	10.0	1		
DÉMONTABILITÉ, ACCÈS, OUTILS,	2.2 Outils nécessaires (liste 2)	10.0	0.5	20.0	
=11/4=10410	2.3 Caractéristiques des fixations entre les pièces de la liste 1** et de la liste 2	10.0	0.5		
	3.1 Durée de disponibilité des pièces de la liste 2	6.0	1		
CRITÈRE 3 : DISPONIBILITÉ DES	3.2 Durée de disponibilité des pièces de la liste 1	0	0.5	8.5	
	3.3 Délais de livraison des pièces de la liste 2	4.0	0.3	6.5	83.4
	3.4 Délais de livraison des pièces de la liste 1	6.3	0.2		
CRITÈRE 4 : PRIX DES PIÈCES DÉTACHÉES	4. Rapport prix des pièces de la liste 2 sur prix de l'équipement neuf	10.0	2	20.0	
	5.1 Accesibilité du compteur d'usage	10.0	1		
CRITÈRE 5 : CRITÈRE SPÉCIFIQUE	5.2 Assistance à distance sans frais	6.0	0.5	18.0	8.0
_	5.3 Possibilité de réinitialisation logicielle	10.0	0.5		
	N	ote de l'i	indice su	ır 10	8.3

<sup>\*</sup>liste 2 : liste des 3 à 5 pièces détachées au maximum (selon la catégorie d'équipements concernée) dont la casse ou les pannes sont les plus fréquentes ;
\*\*liste 1 : liste de 10 autres pièces détachées au maximum (selon la catégorie d'équipements concernée) dont le bon état est nécessaire au fonctionnement de l'équipement.

## ANNEX 1: TERMINOLOGY USED FOR THE REPARABILITY INDEX

The definitions of the following terms are specified in the decree relating to the repairability index for electrical and electronic equipment: "Making available onthe market", "Placing on the market", "producer", "miporter", "distributor", "Seller", "distance selling", "model".


Independent repaires on the more contracts processly deliven the stationary between the summonters repaired and the producent;  Independent repaires and engines in the state of "professional repaires" who are on the technical expertise of independent repaires and engines who do not tall into category of authorized repaires. Or coverage sheet of completes and peripheral equipments of the expertise of independent repaires who do not tall into category of expertise of independent and peripheral equipments of the expertise of independent of peripheral peripheral experts of completes and peripheral experts of the expert of completes and peripheral experts of the experts of the expert of the experts of the expert of the experts of the experts of the experts of the expert of the experts of the experts of the experts of the experts of the experts of the experts of the experts of the expert of the experts of the expe			
issed in the trade directory with an AF or NAFA code. They are professional repairer of authorized regainers, for example, 95 11.2. Regain of computers and perplared supplainers 22.1.2. Regain of prospensional repairer.  Authorized regainers, For example, 95 11.2. Regain of mousehold explainers and home and garden equipment and home and garden equipment.  Authorized regainers with the process of the property of the process of the property of the process of the property of the process of the property of the process of the process of the product, sopre part or fastener is reassembled so that it can then be reassembled and made application of the process by which a product, sopre part or fastener is reassembled so that it can then be reassembled and made application.  Ressembly  The process by which a product, a spare part or a fastener is reassembled so as to fulfill its functional role and be made opposed for which it was disagred. Result and the product process of the product product process of the product process of the product product process of the product product process of the product product process of the product product process of the product product process of the product produc	Authorized repairer		
Disabilitutor of spare parts    Pay mould to physica person in the supply chain, other than the producer or importer, who offers a spare part for sale. They are commonly referred to as "spare parts wholesaless".    Pay are commonly referred to as "spare parts wholesaless".   Pay are commonly referred to as "spare part or fastener is disassembled so that it can then be reassembled and made operational.   Pay process by which a product, a spare part or a fastener is reassembled so as to fulfill its functional role and be made operational.   Pay a process of the product of	Independent repairer	listed in the trade directory with an APE or NAFA code. They are professional repairers who do not fall into the category of authorized repairers. For example, 95.11 Z-Z Repair of computers and peripheral equipment 95.21 Z-Z. Repair of the relevisions, radio receivers, VCRs, CD and DVD players, cambroders for domestic use; 95.22 Z-Z: Repair of household	
Disasembly  The process by which a product, spare part or fastener is disassembled so that it can then be reassembled and made operational.  The process by which a product, spare part or fastener, having reached the end of its first use, is used for the same purpose for which it was designed. Reuse after a second or subsequent use(s) is also considered to be reuse.  Factory Restoration  A specific functionality or setting to be activated by the customer, if the product, allows it, to restore the default value of a specific functionality of the device as set at the factory and available when the customer first uses the product.  The process of improving the functionality, performance, capacity or aesthetics of a product. This process may involve changes to the software, firmware and/or a hardware component of the product.  The process of improving the functionality, performance, capacity or aesthetics of a product. This process may involve changes to the software, firmware and/or a hardware component of the product.  The process of improving the functionality, performance, capacity or aesthetics of a product. This process may involve changes to the software, firmware and/or a hardware component of the product.  The process of improving the functionality, performance, capacity or aesthetics of a product. This process may involve changes to the software, firmware and/or a hardware component of the product.  The process of improving the functionality performance, capacity or aesthetics of a product. This process may involve changes to the software and/or a hardware component of the product.  The process of improving the functionality performance, capacity or aesthetics of a product. This process may involve changes to the software and intended to restore an asset or software to a state in which it can be preformed after a failure has been detected and intended to restore an asset or software to a state in which it can be preformed after a failure has been detected and intended to restore an asset or software to a s	Professional repairer	Authorized repairer or independent repairer.	
perational.  The process by which a product, a spare part or a fastener is reassembled so as to fulfill its functional role and be made operational.  The process by which a product, aspare part or a fastener is reassembled so as to fulfill its functional role and be made operational.  The process by which a product, spare part or fastener, having reached the end of its first use, is used for the same surpose for which it was designed freuze after a second or subsequent use(s) is also condidated to be reuse.  Factory Restoration  A specific functionality or setting to be activated by the customer, if the product allows it, to restore the default value of a specific functionality of the device as set at the factory and available when the customer first uses the product.  The process of improving the functionality, performance, capacity or aesthetics of a product. This process may involve changes to the software, firmware and/or a hardware component of the product.  An update performed after a failure has been detected and intended to restore an asset or software to a state in which it can perform a required function. This type of update corrects hardware or software maillunctions or non-conformity but of son and add new functionality. Design and existing functionality or some part of the product.  Evolutionary update  Dipgrading, which consists of gradually modifying the software application by adding new features or additional modules, or by replacing an existing function with another, or application by proposing a different approach.  Fastener  Dipgrading, which consists of gradually modifying the software application by adding new features or additional meritorion diministry or replication with another provided or disassembled without damaging the objects, parts or pieces. A fastener is generally non-permanent, i.e., it can be easily removed or disassembled without damaging the objects parts or pieces. A fastener is generally non-permanent, i.e., it can be easily removed or disassembled without damaging the ob	Distributor of spare parts		
Reuse / Reusable  The process by which a product, spare part or fistener, having reached the end of its first use, is used for the same surpose for which it was designed. Reuse after a second or subsequent use(s) is also considered to be reuse.  A specific functionality or setting to be activated by the outcomer, if the product allows it, to restore the default value of specific functionality of the device as set at the factory and available when the customer first uses the product.  The process of improving the functionality, performance, capacity or aesthetics of a product. This process may involve changes to the software, firmware and/or a hardware component of the product.  According to Standard NFEN 45554 "General methods for the capacity of the software, firmware and/or a hardware component of the product.  An update performed after a failure has been detected and intended to restore an asset or software to a state in which it can perform a required function. This type of update corrects hardware or software maillunctions or non-conformity but does not add new functionality.  Evolutionary update  Dipgrading, which consists of gradually modifying the software application by adding new features or additional modules, or by replacing an existing function with another, or even by proposing a different approach.  A hardware device that mechanically or magnetically connects or fixes two or more objects, parts or pieces. A fastener is generally non-permanent, i.e., it can be easily removed or disassembled without damaging the objects, parts or pieces. Profrom the required function.  A hardware device that mechanically or magnetically connects or fixes two or more objects, parts or pieces. Profrom the required function.  Fastener  See the definition of "reusable".  A hardware device that mechanically or magnetically connects or fixes two or more objects, parts or pieces. A fastener is generally non-permanent, i.e., it can be easily removed or disassembled without damaging the objects. Profrom the required functio	Disassembly		45554 "General methods for the
Reuse / Reusable  The process by which a product, spare part or fastener, having reached the end of its first use, is used for the same outgoes for which it was designed. Reuse after a second to subsequent use(s) considered to be reuse.  A specific functionality or setting to be activated by the customer, if the product allows it, to restore the default value of a specific functionality of the device as set at the factory and available when the customer first uses the product.  The process of improving the functionality, performance, capacity or aesthetics of a product. This process may involve charges to the software, firmware and/or a hardware component of the product.  The process of improving the functionality, performance, capacity or aesthetics of a product. This process may involve charges to the software, firmware and/or a hardware component of the product.  An update performed after a failure has been detected and intended to restore an asset or software to a state in which it can perform a required function. This type of update corrects hardware or software malfunctions or non-conformity but 1330 × 160-319 standard of Name on the software application by adding new features or additional modules, or by replacing an existing function with another, or even by proposing a different approach.  Fastener  A hardware device that mechanically or magnetically connects or fixes two or more objects, parts or pieces. A fastener is generally non-permanent, i.e., it can be easily removed or disassembled without damaging the objects, parts or pieces promited or fixed together (e.g., screw or clips). Welds and some glues are in contrast to permanent fixings. Adhesives sometime or magnetically or magnetic	Reassembly		improvement capacity of energy-
Update / Upgrade  The process of improving the functionality, performance, capacity or aesthetics of a product. This process may involve changes to the software, firmware and/or a hardware component of the product.  According to Standard NF EN 45554 "General methods for the design proving the functionality, performance, capacity or aesthetics of a product. This process may involve changes to the software, firmware and/or a hardware component of the product.  An update performed after a failure has been detected and intended to restore an asset or software to a state in which it can perform a required function. This type of update corrects hardware or software maifunctions or non-conformity but 13306 x 60-319 standard of Jube con or add ene functionality.  Evolutionary update  Upgrasing, which consists of gradually modifying the software application by adding new features or additional modules, or by replacing an existing function with another, or even by proposing a different approach.  A hardware device that mechanically or magnetically connects or fives two or more offerent approach.  A hardware device that mechanically or magnetically connects or five store	Reuse / Reusable	The process by which a product, spare part or fastener, having reached the end of its first use, is used for the same purpose for which it was designed. Reuse after a second or subsequent use(s) is also considered to be reuse.	related products , 2020.
The process of improving the functionality, performance, capacity or aesthetics of a product. This process may involve changes to the software, firmware and/or a hardware component of the product.  An update performed after a failure has been detected and intended to restore an asset or software to a state in which it can perform a required function. This type of update corrects hardware or software malfunctions or non-conformity but 1330 × 06-319 standard of June Evolutionary update  Upgrading, which consists of gradually modifying the software application by adding new features or additional modules, or by replacing an existing function with another, or even by proposing a different approach.  A hardware device that mechanically or magnetically connects or fixes two or more objects, parts or pieces. A fastener is generally non-permanent, i.e., it can be easily removed or disassembled without damaging the objects, parts or pieces. A fastener is generally non-permanent, i.e., it can be easily removed or disassembled without damaging the objects, parts or pieces. A fastener is generally non-permanent, i.e., it can be easily removed or disassembled without damaging the objects, parts or pieces. A fastener is generally non-permanent i.e., it can be easily removed or disassembled without damaging the objects, parts or pieces. A fastener is generally non-permanent i.e., it can be easily removed or disassembled without damaging the objects, parts or pieces, existed and the part of the pa	Factory Restoration		
corrective update  can perform a required function. This type of update corrects hardware or software malifunctions or non-conformity but does not add new functionality.  1 (1) (1) (2) (2) (2) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3	Update / Upgrade		45554 "General methods for the evaluation of the repair, reuse and improvement capacity of energy-
Dipgrading, which consists of gradually modifying the software application by adding new features or additional modules, or by replacing an existing function with another, or even by proposing a different approach.    A hardware device that mechanically or magnetically connects or fixes two or more objects, parts or pieces. A fastener is generally non-permanent, i.e., it can be easily removed or disassembled without damaging the objects, parts or pieces. A fastener is generally non-permanent, i.e., it can be easily removed or disassembled without damaging the objects, parts or pieces. A fastener is generally non-permanent, i.e., it can be easily removed or disassembled without damaging the objects, parts or pieces. A fastener is generally non-permanent, i.e., it can be easily removed or disassembled without damaging the objects, parts or pieces. A fastener is generally non-permanent, i.e., it can be easily removed or disassembled without damaging the objects, parts or pieces. A fastener is generally non-permanent, parts or pieces. A fastener is generally non-permanent, parts or pieces. A fastener is generally non-permanent, parts or pieces. A fastener is generally non-permanent, parts or pieces. A fastener is generally non-permanent fixings. Adhesives in Types'; Bright Hub Engineering, 2020.    According to Standard NFEN   ASS4* General methods for the evolution of the repair, reuse and the repair reuse and provinces. A proprietarly residuely or deeply-related provinces. 2020.    According to Standard NFEN   ASS4* General methods for the evolution of the repair, reuse and provinces. A proprietarly residuely or deeply-related provinces. 2020.    According to Standard NFEN   ASS4* General methods for the evolution of the repair, reuse and provinces. A proprietarly residuely or deeply-related provinces. 2020.    According to Standard NFEN   ASS4* General methods for the evolution of the repair reuse and provinces. 2020.    According to Standard NFEN   ASS4* General methods for the evolution of the repair reuse a	Corrective update	can perform a required function. This type of update corrects hardware or software malfunctions or non-conformity but	13306 X 60-319 standard of June 2011 "All the technical, administrative and management
Pastener openerally non-permanent, i.e., it can be easily removed or disassembled without damaging the objects, parts or pieces connected or fixed together (e.g., servers or clips). Welds and some glues are in contrast to permanent fixings. Adhesives are considered non-reusable fasteners unless new ones are supplied with the spare part.  According to Standard NFEN 45554 "General methods for the evaluation of the repair, reuse and methods for the evaluation of the repair, reuse and prevented appears of energy-related products", 2020.  Removable fastener  An original fastener system that can be completely removed (without causing damage or leaving residue).  Proprietary tool  A tool that is not commercially available and is owned exclusively by one party or company, and under which its use by another party (an end user or customer) involves copyright, license and/or cost.  "Proprietary Een holdogy", 2019.	Evolutionary update	Upgrading, which consists of gradually modifying the software application by adding new features or additional modules, or by replacing an existing function with another, or even by proposing a different approach.	asset, intended to maintain or restore it to a state in which it can
Reusable fastener  See the definition of "reusable".  See the definition of "reusable".  See the definition of "reusable".  See the definition of "reusable".  See the definition of "reusable".  See the definition of "reusable".  See the definition of "reusable".  See the definition of "reusable".  See the definition of "reusable".  An original fastener system that can be completely removed (without causing damage or leaving residue).  Proprietary tool  A tool that is not commercially available and is owned exclusively by one party or company, and under which its use by another party (an end user or customer) involves copyright, license and/or cost.  "Proprietary Technology", 2019.	Fastener	generally non-permanent, i.e., it can be easily removed or disassembled without damaging the objects, parts or pieces connected or fixed together (e.g., screws or clips). Welds and some glues are in contrast to permanent fixings. Adhesives	Needs and Types", Bright Hub
A tool that is not commercially available and is owned exclusively by one party or company, and under which its use by another party (an end user or customer) involves copyright, license and/or cost.  "Proprietary Technology", 2019.	Reusable fastener	See the definition of "reusable".	45554 "General methods for the evaluation of the repair, reuse and improvement capacity of energy-
another party (an end user or customer) involves copyright, license and/or cost. "Proprietary Technology", 2019.	Removable fastener	An original fastener system that can be completely removed (without causing damage or leaving residue).	
Part / Spare parts A unitary element in the composition of the equipment.	Proprietary tool		
	Part / Spare parts	A unitary element in the composition of the equipment.	

## ANNEX 2: BASIC TOOLS AND THEIR REFERENCE STANDARDS

According to the European Standard NF EN 45554 "General methods for the assessment of the ability to repair, reuse and upgrade energy-related products", 2020.

Tool type	Illustration (informative example)	Reference
Screwdriver for slotted heads, cross recess or for hexalobular recess heads		ISO 2380, ISO 8764, ISO 10664
Hexagon socket key		ISO 2936
Combination wrench		ISO 7738
Combination pliers		ISO 5746
Half round nose pliers		ISO 5745
Diagonal cutters		ISO 5749
Multigrip pliers (multiple slip joint pliers)		ISO 8976
Locking pliers		

	ı	ı
Combination pliers for wire stripping and terminal crimping		
Prying lever	5	
Tweezers		
Hammer, steel head		SO 15601
Utility knife (cutter) with snap-off blades		
Multimeter		
Voltage tester		
Soldering iron		
Hot glue gun		



# ANNEX 3: DETAILS ABOUT THE CONCEPT OF DISASSEMBLY STEP A

# **ND APPLICATION CASE**